Description 4.162 acre parcel

Being part of the southeast quarter of Fractional Section 18, T-8 N, R-6 W, Mechanic Township, Holmes County, Ohio.

Described as follows:

Beginning at a R.R. spike found in C.R. 59 marking the southeast corner of the southeast quarter of Fractional Section 18 the TRUE POINT OF BEGINNING, witnessed by a 5/8 inch rebar found N 00 degrees 51' 42" E 12.64 feet.

thence with the following FOUR (4) COURSES:

- 1) N 89 degrees 16' 05" W 676.08 feet along the section line and along C.R. 59 to a point, witnessed by an iron pin set N 00 degrees 51' 42" E 2.96 feet;
- 2) N 00 degrees 51' 42" E 268.19 feet to an iron pin set;
- 3) S 89 degrees 16' 05" E 676.08 feet to an iron pin set on the section line;
- 4) S 00 degrees 51' 42" W 268.19 feet along the section line to the TRUE POINT OF BEGINNING.

This parcel contains 4.162 acres, but subject to all highways and easements of record.

All iron pins set are 5/8 inch rebars with a plastic identification cap marked "Baker 6938"; Basis of bearings from Ohio State Plane Coordinate System, North Zone, N.A.D. 83, 2011 adjustment.

19 , page 5402 for survey. See Holmes County Plat Book_ This survey made and description prepared by Donald C. Baker, P.S. 6938. July 29, 2024

P.S. 6938

Baker

Baker

DONA'

DONA'

PPN: 1300393010