LINGENFELTER SURVEYING, LLC

PROFESSIONAL LAND SURVEYING

Boundary description of a 3.540 acre parcel:

22-025

Situated in the Township of Prairie, T-13N; R-13W, Northeast Quarter of Section 6, County of Holmes, and State of Ohio:

Known as being the lands conveyed to Daniel M. Weaver & Betty Weaver in Volume 220; Page 890, (PPN. 1700499002), of Holmes County Deed Records and further bounded and described as follows:

Commencing at 5/8 inch rebar with I.D. cap "Baker" found and being the southwest corner of the Northeast Quarter of Section 6;

Thence, S 89° 31' 12" E, 629.51 feet along the quarter section line to a 5/8 inch rebar with I.D. cap "REK-5193" found and the principal place of beginning of the parcel herein described:

THENCE WITH THE FOLLOWING NINE (9) COURSES:

- 1. N 00° 30' 50" E, 316.78 feet along the Grantor's westerly line and the easterly line of the lands conveyed to Leroy E. Yoder & Naomah D. Yoder, (O.R. V-249, P-1743, PPN. 1700499001), to a 5/8 inch rebar with I.D. cap "Baker" found;
- 2. N00° 27' 18" E, 285.48 feet along the Grantor's westerly line and the easterly line of the lands conveyed to Leroy E. Yoder & Naomah D. Yoder, (O.R. V-254, P-4683, PPN. 1700499005), to a 5/8 inch rebar with I.D. cap "Baker" found;
- 3. **S 89° 27' 28" W, 138.13** feet along the Grantor's southerly line and the northerly line of said Yoder lands to a MAG nail set in Township Road 553, (60 foot right of way), witnessed by a capped rebar set N 89° 27' 28" E, 12.00 feet;
- 4. N 07° 01' 12" E, 50.40 feet along the Grantor's westerly line and with Township Road 553 to a MAG nail set witnessed by a capped rebar set N 89° 27' 28" E, 12.00 feet;
- 5. N 89° 27' 28" E, 427.43 feet along the Grantor's northerly line and the southerly line of the lands conveyed to Michael L. Yoder & Martha L. Yoder, (O.R. V-202, P-1521, PPN. 1700499002), to a capped rebar set;

Continued on Page 2



Page 2 (Description of 3.540 ac.)

- 6. S 00° 28' 08" E, 150.00 feet along the Grantor's easterly line and the westerly line of said Yoder lands to a 5/8 inch rebar found;
- 7. N 89° 25' 06" W, 97.01 feet along the Grantor's southerly line and the northerly line of said Yoder lands to a 5/8 inch rebar with I.D. cap "Baker" found;
- 8. S 00° 27' 11" E, 507.76 feet along the Grantor's easterly line and the westerly line of said Yoder lands to a 5/8 inch rebar with I.D. cap "Baker" found on the quarter section line;
- 9. **N 89° 31' 12" W, 208.80** feet along the quarter section line and the Grantor's southerly line to the principle place of beginning and containing within said bounds **3.540** acres of land, more or less, and subject to all legal highways and easements of record.

This description was prepared from a survey made by Jason J. Lingenfelter, P.S. #8499 of Lingenfelter Surveying, LLC in July of 2022.

All rebars set are 5/8"diameter by 30" long with plastic cap stamped "LINGENFELTER".

Basis of bearing: The bearings as shown hereon are relative to GRID NORTH of the OHIO STATE PLANE COORDINATE SYSTEM, NAD 83 (2011) DATUM.

See Holmes County Plat Volume _____; Page ______ for survey.

Jason J. Lingenfelter, P.S

July 18, 2022

Parcel Number: 1700499006

JASON J.
LINGENFELTER &
8499

TS ONAL SHE

FILE DESCRIPTION

Holmes County Map Office 8/24/2022