

No 458

Legal Survey Notice.

To John McMurtry, Geo Stutz and Chenevey

You are hereby notified that a survey will be made and testimony taken by the county Surveyor of Holmes County Ohio, on the 13th day of December 1892 between the hours of 10 A.M. and 4 P.M., and to continue from time to time at the request of said County Surveyor until the lines boundaries and corners of the following described tract of land, now owned and held by Geo Stutz et al and situate in Saltcreek township, Holmes County, Ohio, can be established:

Being the northeast quarter of the northeast quarter of Section 26, Twp. 15, R. 12.

Interested parties are hereby notified to give said Surveyor the names of witnesses they wish subpoenaed and to be present at said survey.

Signed this 19th day of Nov. 1892,

Geo Stutz.

State of Ohio Holmes Co., H.S.

Eugene Stutz being first duly sworn states that on the 21st day of November, 1892, and at least 20 days before December 13th 1892, he served copies of the foregoing notice on each of the above named parties

(signed) Eugene Stutz.

Sworn to and subscribed before me this 14th day of December, 1892.

Frank H. Gove,
County Surveyor.

On the 13th day of December 1892, I proceeded to the premises above described for the purpose of making the survey. Owing to the unfavorable weather we postponed the Survey till the next day, the 14th day of Dec, 1892.

On the 14th day of Dec, 1892, we began the survey, selecting Victor J. Martin and Joseph E. Martin, as chairmen, acceptable to all parties interested. They were duly sworn.

The Southwest corner of the northeast quarter of the N.E. Tr., being the one in dispute established the same by establishing the corner F on the west line of the quarter section half way between E and G, as they were good corners. The corner D and H being good, at the intersection of line from D to H with line from F to B, we planted a large boulder at I for the southwest corner of said NE 1/4 NE Tr sec 26. (B being a stone in the public road at the southeast corner said Quarter Quarter) Also planted sand stone at F, so that each quarter quarter corner is now well marked with a good stone.

The corners represented by the above letters refer to the plat on the next page.