

R = 525.41'  
 Δ = 53°53'46"  
 L = 494.24'  
 Chd. = 476.22'  
 S-17°25'49"-W


R = 525.41'  
 Δ = 26°56'53"  
 L = 247.12'  
 Chd. = 244.85'  
 S-30°54'16"-W

R = 525.41'  
 Δ = 26°56'53"  
 L = 247.12'  
 Chd. = 244.85'  
 N-03°57'23"-E

R = 175.00'  
 Δ = 22°21'20"  
 L = 68.28'  
 Chd. = 67.85'  
 N-01°39'36"-E

R = 30.00'  
 Δ = 71°14'15"  
 L = 37.30'  
 Chd. = 34.94'  
 N-22°46'52"-W

R = 175.00'  
 Δ = 13°39'09"  
 L = 41.70'  
 Chd. = 41.60'  
 N-19°39'50"-E



- - Iron Pipe Or Pin Fd.
- - 5/8" x 30" Rebar With Yellow Plastic Cap Marked RUDOLPH Set 6449

I Certify This Survey And Plat To Be Correct To The Best Of My Knowledge.

*Ronald G. Rudolph*  
 1-10-85

Reference Surveys

Previous R.G.R. Surveys In The SW Qtr. Of Section 1 Of 12.000 Ac., 9.920 Ac. And 9.980 Ac.

145735

Date: Ronald G. Rudolph - Reg. Surv. 6449  
 R.G. RUDOLPH SURVEYING, Inc.  
 405 W. Liberty St.  
 Wooster, Ohio 44691

JAN 18 1985  
 Rec'd. AT 2:26 O'CLOCK PM  
 Recorded Jan 22 1985 Holmes Co. Ohio Fee: 10.80  
 Plat Vol. 11 Pg. 26 Recorder Richard Bravens  
 18x12x5=10.80 Deed Vol. 226-Pg. 91

MAP OFFICE COPY