

# SURVEY PLAT of a 1.907 ACRE PARCEL

149177

Of Which 1.554 Acres Is Part Of Lot 12

Third Quarter

And Of Which 0.353 Acres Is Part Of Lot 20

Fourth Quarter

T-10-N, R-6-W

Salt Creek Township

HOLMES COUNTY, OHIO


Sec. 8

Greenville Treaty Line  
821.6'


### References

- Deed Vol. 227, Pg. 572
- Plat Vol. 7, Pg. 221
- Plat Vol. 10, Pg. 254
- Surv. Rec. Bk. 3, Pg. 387
- Surv. Rec. Bk. 4, Pg. 93
- Surv. Rec. Bk. 4, Pg. 110
- Surv. Rec. Bk. 5, Pg. 277

Grantor: Vivian Hershberger  
Deed Vol. 227, Pg. 572



Scale: 1" = 100'



N-00°45'00"-E

149177

NOV 5 1985  
 Rec'd. AT 10:49 o'clock AM  
 Recorded Nov 5, 1985 Holmes Co. Ohio Fees 10.80  
 Plat Vol. 11 Pg. 52 Recorder Richard Brown  
 18x12x15  
 Deed Vol. 229-Pg. 286



I Certify This Survey And Plat To Be  
Correct To The Best Of My Knowledge.

10.28.85 Ronald G. Rudolph  
 Date Ronald G. Rudolph P.S. No. 6449  
 R.G. RUDOLPH SURVEYING, Inc.  
 405 W. Liberty St.  
 Wooster, Ohio 44691



- Stone Corner Fd.
- Iron Pipe Fd.
- △ 5/8" x 15" Rebar Set In Roadway
- 5/8" x 30" Rebar With Yellow Plastic Cap Marked RUDOLPH Set 6449

SE Corner Lot 12  
 Stone Corner Fd. Laying Over. Set Upright Rebar & Cap Set On W. Side Leaning Over To Guard. Old Corner Post Hole On W. Side of Stone.  
 20" Syc. SE 29.5'  
 Twin 18" R. Oak SE 12.4'  
 Fence Cor. Post W. 2.3'

SW Corner Lot 20  
 Stone Corner Fd.  
 Rebar & Cap Set On West Side Leaning Over To Guard

Note: Record Distances Between Lot Corners

- 4 Rods = 66'
- 4 Rods 1 lks = 66.66'
- 4 Rods 6 lks = 69.96'
- 4 Rods 8 lks = 71.28'

MAP OFFICE COPY